



NIELSEN

SAFETY DATA SHEET CLEAR LUBE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEAR LUBE

Product number A1745/01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier NIELSEN CHEMICALS
RAWDON ROAD
MOIRA
SWADLINCOTE
DERBYSHIRE
DE12 6DA
info@nielsenchemicals.com
TEL: +44 (0) 1283 222277
FAX: +44 (0) 1283 550621

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R38. F+;R12. N;R51/53. R67.

2.2. Label elements

Pictogram



Signal word

Danger

CLEAR LUBE

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves. P312 Call a POISON CENTER/doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container in accordance with national regulations.
Contains	HEPTANE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBON PROPELLANT 30-60%		
CAS number: 68476-85-7	EC number: 270-704-2	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12.	
HEPTANE 10-30%		
CAS number: —	EC number: 927-510-4	REACH registration number: 01-2119475515-33-xxxx
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
WHITE MINERAL OIL (PETROLEUM) 10-30%		
CAS number: 8042-47-5	EC number: 232-455-8	REACH registration number: 01-2119487078-27-XXXX
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

CLEAR LUBE

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable aerosol. Pressurised container: may burst if heated
Hazardous combustion products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
---	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

CLEAR LUBE

Usage precautions Keep away from heat, sparks and open flame. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Store at temperatures between 4°C and 40°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBON PROPELLANT

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

HEPTANE

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

Short-term exposure limit (15-minute): WEL No std.

WEL = Workplace Exposure Limit

HEPTANE

DNEL

Industry - Dermal; Long term : 300 mg/kg/day

Industry - Inhalation; Long term : 2085 mg/m³

Consumer - Dermal; Long term : 149 mg/kg/day

Consumer - Inhalation; Long term : 447 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Hydrocarbons.

Solubility(ies) Insoluble in water.

9.2. Other information

Other information No information required.

CLEAR LUBE

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish Not determined.

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

CLEAR LUBE

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

ADR/RID packing group 5F

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

CLEAR LUBE

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
-----------------------	--

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	24/06/2015
Revision	1.3
Supersedes date	24/04/2013
Risk phrases in full	R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.