



NIELSEN

SAFETY DATA SHEET SILVER WHEEL PAINT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SILVER WHEEL PAINT

Internal identification B085

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wheel paint.

1.3. Details of the supplier of the safety data sheet

Supplier NIELSEN CHEMICALS
 RAWDON ROAD
 MOIRA
 SWADLINCOTE
 DERBYSHIRE
 DE12 6DA
 TEL: +44 (0) 1283 222277
 FAX: +44 (0) 1283 225731
 info@nielsenchemicals.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs). +44 (0) 1865 407333 (24 hrs). MEDICAL AND ENVIRONMENTAL EMERGENCIES ONLY.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word

Danger

SILVER WHEEL PAINT

Hazard statements	<p>H222 Extremely flammable aerosol.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P280 Wear protective clothing, gloves, eye and face protection.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	ACETONE, XYLENE, EPOXY RESIN (Number average MW ≤ 700), Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE	30-60%
CAS number: 67-64-1	EC number: 200-662-2
	REACH registration number: 01-2119471330-49-xxxx
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
HYDROCARBON PROPELLANT	30-60%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	
Flam. Gas 1 - H220	
Press. Gas (Liq.) - H280	

SILVER WHEEL PAINT

XYLENE	10-30%
CAS number: 1330-20-7	EC number: 215-535-7
REACH registration number: 01-2119488216-32-XXXX	
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
EPOXY RESIN (Number average MW <= 700)	5-10%
CAS number: 25068-38-6	EC number: 500-033-5
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
ETHYLBENZENE	1-5%
CAS number: 100-41-4	EC number: 202-849-4
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	1-5%
CAS number: 64742-48-9	EC number: 927-241-2
REACH registration number: 01-2119471843-32-XXXX	
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

SILVER WHEEL PAINT

Eye contact Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Extremely flammable aerosol. Pressurised container: may burst if heated

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting In case of fire: Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Avoid inhalation of vapours. Do not enter storage areas or confined spaces unless adequately ventilated. Do not touch or walk into spilled material. Take precautionary measures against static discharges. Avoid contact with contaminated tools and objects. Do not handle broken packages without protective equipment. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

SILVER WHEEL PAINT

7.1. Precautions for safe handling

Usage precautions Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Avoid breathing vapour/spray. Avoid contact with contaminated tools and objects. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use. Do not empty into drains. Do not eat, drink or smoke when using this product. Do not handle broken packages without protective equipment. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not expose to temperatures exceeding 50°C/122°F. Store at temperatures between 4°C and 40°C.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

HYDROCARBON PROPELLANT

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Long-term exposure limit (8-hour TWA): 1000 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

ACETONE (CAS: 67-64-1)

DNEL

Industry - Dermal; Long term : 186 mg/kg/day

Industry - Inhalation; Short term : 2420 mg/m³

Industry - Inhalation; Long term : 1210 mg/m³

Consumer - Oral; Long term : 62 mg/kg/day

Consumer - Dermal; Long term : 62 mg/kg/day

Consumer - Inhalation; Long term : 200 mg/m³

SILVER WHEEL PAINT

PNEC	- Fresh water; 10.6 mg/l
	- Marine water; 1.06 mg/l
	- water; 21 mg/l
	- Sediment; 3.04 mg/kg
	- Soil; 33.3 mg/l
	- STP; 29.5 mg/l

XYLENE (CAS: 1330-20-7)

DNEL	Industry - Inhalation; Short term : 442 mg/m ³
	Industry - Inhalation; Long term : 221 mg/m ³
	Industry - Dermal; Long term : 3182 mg/kg/day
	Consumer - Inhalation; Short term : 260 mg/m ³
	Consumer - Inhalation; Long term : 65.3 mg/m ³
	Consumer - Dermal; : 1872 mg/kg/day
	Consumer - Oral; Long term : 12.5 mg/kg/day

PNEC	- Fresh water; 0.327 mg/l
	- Marine water; 0.327 mg/l
	- Sediment (Freshwater); 12.46
	- Sediment (Marinewater); 12.46 mg/l
	- Soil; 2.31 mg/kg
	- STP; 6.58 mg/l

ETHYLBENZENE (CAS: 100-41-4)

DNEL	Workers - Inhalation; Long term systemic effects: 77 mg/m ³
	Workers - Inhalation; Short term local effects: 293 mg/m ³
	Workers - Dermal; Long term systemic effects: 180 mg/kg/day
	General population - Inhalation; Long term systemic effects: 15 mg/m ³
	General population - Oral; Long term systemic effects: 1.6 mg/kg/day

PNEC	- Fresh water; 0.1 mg/l
	- Marine water; 0.01 mg/l
	- Intermittent release; 0.1 mg/l
	- STP; 9.6 mg/l
	- Sediment (Freshwater); 13.7 mg/kg/day
	- Sediment (Marinewater); 1.37 mg/kg/day
- Soil; 2.68 mg/kg/day	

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)

DNEL	Industry - Dermal; systemic effects: 300 mg/kg/day
	Industry - Inhalation; systemic effects: 1500 mg/m ³
	Consumer - Dermal; systemic effects: 300 mg/m ³
	Consumer - Inhalation; systemic effects: 900 mg/m ³
	Consumer - Oral; systemic effects: 300 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation.

SILVER WHEEL PAINT

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Personal protective equipment for eye and face protection should comply with European Standard EN166. The following protection should be worn: The following protection should be worn: Tight-fitting safety glasses. Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Protective gloves should have a minimum thickness of 0.12 mm. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Gloves made from the following material may provide suitable chemical protection: Neoprene. Nitrile rubber. Rubber (natural, latex). The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application.
Hygiene measures	Wash skin thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Silver.
Odour	Acetone. Ketonic. Hydrocarbons.
Solubility(ies)	Insoluble in water.

9.2. Other information

Other information	No information required.
--------------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
---	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

SILVER WHEEL PAINT

10.5. Incompatible materials

Materials to avoid Flammable/combustible materials. Flammable/combustible materials.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances:
Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 7,051.28

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 42.31

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Toxicological information on ingredients.

ACETONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 15,800.0

Species Rat

ATE dermal (mg/kg) 15,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 76.0

Species Rat

ATE inhalation (vapours mg/l) 76.0

HYDROCARBON PROPELLANT

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.6

SILVER WHEEL PAINT

Species	Rat
ATE inhalation (vapours mg/l)	21.6

XYLENE**Acute toxicity - dermal****Notes (dermal LD₅₀)**

ATE dermal (mg/kg)	1,100.0
---------------------------	---------

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)	20.0
---	------

Species	Rat
----------------	-----

ATE inhalation (vapours mg/l)	20.0
--------------------------------------	------

ETHYLBENZENE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg)	5,460.0
--	---------

Species	Rat
----------------	-----

ATE oral (mg/kg)	5,460.0
-------------------------	---------

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg)	2,001.0
--	---------

Species	Rabbit
----------------	--------

ATE dermal (mg/kg)	2,001.0
---------------------------	---------

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)	12.0
---	------

Species	Rat
----------------	-----

ATE inhalation (vapours mg/l)	12.0
--------------------------------------	------

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg)	5,001.0
--	---------

Species	Rat
----------------	-----

ATE oral (mg/kg)	5,001.0
-------------------------	---------

Acute toxicity - dermal

SILVER WHEEL PAINT

Acute toxicity dermal (LD₅₀ 2,001.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 5,080.0

Species Rat

ATE inhalation (vapours mg/l) 5,080.0

SECTION 12: Ecological Information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Ecological information on ingredients.

ACETONE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 11000 (Alburnus alburnus) mg/l, Fish

Acute toxicity - aquatic plants NOEC, 96 hours: 430 mg/l, Freshwater algae

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 8 day: 2212 mg/l, Daphnia magna

XYLENE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 4.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 2.93 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 2.2 mg/l, Algae

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 11 mg/l, Pimephales promelas (Fat-head Minnow)

Chronic aquatic toxicity

Chronic toxicity - fish early life stage LL₅₀, 48 hours: 5.2 mg/l, Pimephales promelas (Fat-head Minnow)

SILVER WHEEL PAINT

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

Ecological information on ingredients.

ACETONE

Persistence and degradability Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Ecological information on ingredients.

ACETONE

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

Special Provisions note

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

IMDG class 2.1

SILVER WHEEL PAINT

ICAO class/division 2.1

Transport labels



14.4. Packing group

ADR/RID packing group 5F

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Control of Substances Hazardous to Health Regulations 2002 (as amended).
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation

Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).
Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.
Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

SILVER WHEEL PAINT

Abbreviations and acronyms used in the safety data sheet	<p>ATE: Acute Toxicity Estimate.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>GHS: Globally Harmonized System.</p> <p>IATA: International Air Transport Association.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</p> <p>MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>UN: United Nations.</p>
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	07/02/2018
Revision	3.0
Supersedes date	26/06/2015
SDS number	26443
Hazard statements in full	<p>H220 Extremely flammable gas.</p> <p>H222 Extremely flammable aerosol.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.</p> <p>H373 May cause damage to organs (Central nervous system, Kidneys, Liver) through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.