



NIELSEN

SAFETY DATA SHEET SPRAYWAX

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SPRAYWAX

Internal identification L025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish.

1.3. Details of the supplier of the safety data sheet

Supplier

NIELSEN CHEMICALS
 RAWDON ROAD
 MOIRA
 SWADLINCOTE
 DERBYSHIRE
 DE12 6DA
 info@nielsenchemicals.com
 TEL: +44 (0) 1283 222277
 FAX: +44 (0) 1283 225731

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs). +44 (0) 1865 407333 (24 hrs). MEDICAL AND ENVIRONMENTAL EMERGENCIES ONLY.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 STOT RE 1 - H372

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) R10,R52/53,R66.

2.2. Label elements

Pictogram



Signal word

Danger

SPRAYWAX

Hazard statements	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/ doctor if you feel unwell. P501 Dispose of contents/ container in accordance with national regulations. P280 Wear protective gloves.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	10-30%
CAS number: 64742-82-1	EC number: 919-446-0
	REACH registration number: 01-2119458049-33-0000
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. N;R51/53. R10,R66,R67.
ISOPARAFFINIC HYDROCARBON	1-5%
CAS number: —	EC number: 923-037-2
	REACH registration number: 01-2119471991-29-XXXX
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 Aquatic Chronic 4 - H413	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R53,R66.
TREATED KAOLIN	<1%
CAS number: 1332-58-7	EC number: 310-127-6
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -

SPRAYWAX

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Use suitable lotion to moisturise skin.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause drowsiness or dizziness.
Ingestion	Central nervous system depression.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take care as floors and other surfaces may become slippery. No smoking, sparks, flames or other sources of ignition near spillage. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Provide adequate ventilation. Take precautionary measures against static discharges. Wash thoroughly after dealing with a spillage.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Harmful to aquatic life with long lasting effects.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

SPRAYWAX

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Eliminate all sources of ignition. Take precautionary measures against static discharges. Wear protective gloves. Use only outdoors or in a well-ventilated area. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Avoid release to the environment. Do not reuse empty containers. Do not empty into drains. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 4°C and 40°C. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

ISOPARAFFINIC HYDROCARBON

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m³

TREATED KAOLIN

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

WEL = Workplace Exposure Limit

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)

DNEL

Workers - Inhalation; Long term systemic effects: 330 mg/m³
 Workers - Dermal; Long term systemic effects: 44 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 71 mg/m³
 Consumer - Dermal; Long term systemic effects: 26 mg/kg/day
 Consumer - Oral; Long term systemic effects: 26 mg/kg/day

ISOPARAFFINIC HYDROCARBON

SPRAYWAX

DNEL	Industry - Inhalation; : N/A Industry - Dermal; : N/A Consumer - Inhalation; : N/A Consumer - Dermal; : N/A Consumer - Oral; : N/A
PNEC	- Fresh water; N/A - Marine water; N/A - Soil; N/A - Sediment; N/A - STP; N/A - Intermittent release; N/A

8.2. Exposure controls

Protective equipment



Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: > 0.46 mm Neoprene. Thickness: > 0.54 mm Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Hygiene measures

Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Creamy liquid.
Colour	Violet.
Odour	Characteristic.
pH	Not applicable.
Flash point	42°C SCC (Setaflash closed cup).
Relative density	0.920 @ 20°C
Solubility(ies)	Emulsible in water.
Viscosity	10-20k cP @ 20°C

9.2. Other information

Other information	Not determined.
--------------------------	-----------------

SPRAYWAX

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Specific target organ toxicity - repeated exposure

Target organs Central nervous system

Inhalation May cause drowsiness or dizziness.

Ingestion Central nervous system depression.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May cause discomfort.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,400.0

Species Rat

ATE dermal (mg/kg) 3,400.0

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 1056 mg/kg, Oral, Rat

SPRAYWAX

Target organs	Central nervous system
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways.

ISOPARAFFINIC HYDROCARBON

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
Notes (oral LD₅₀)	Estimated value.
ATE oral (mg/kg)	5,000.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	5,000.0
Species	Rat
ATE dermal (mg/kg)	5,000.0
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Estimated value.

SECTION 12: Ecological Information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish Not determined.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute toxicity - fish LC₅₀, 96 hours: <30 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: <22 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 4.6-10 mg/l, Fish

Acute toxicity - microorganisms EC₅₀, 48 hours: 43.98 mg/l,

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.097 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

SPRAYWAX

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Persistence and degradability The product is not readily biodegradable.

ISOPARAFFINIC HYDROCARBON

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

ISOPARAFFINIC HYDROCARBON

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is partly miscible with water and may spread in the aquatic environment.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Surface tension 0.02 mN/m @ 25°C

ISOPARAFFINIC HYDROCARBON

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

ISOPARAFFINIC HYDROCARBON

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

ISOPARAFFINIC HYDROCARBON

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SPRAYWAX

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

Special Provisions note

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

SPRAYWAX

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.
Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ATE: Acute Toxicity Estimate.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service.
DNEL: Derived No Effect Level.
IATA: International Air Transport Association.
IMDG: International Maritime Dangerous Goods.
PBT: Persistent, Bioaccumulative and Toxic substance.
PNEC: Predicted No Effect Concentration.
vPvB: Very Persistent and Very Bioaccumulative.
NOAEL: No Observed Adverse Effect Level.
NOEC: No Observed Effect Concentration.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 14/12/2016

Revision 4.1

Supersedes date 26/08/2016

Risk phrases in full Not classified.
R10 Flammable.
R22 Harmful if swallowed.
R38 Irritating to skin.
R41 Risk of serious damage to eyes.
R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53 May cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.