



NIELSEN

SAFETY DATA SHEET SUPER A-SHEEN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SUPER A-SHEEN

Internal identification L431

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Finish coat.

Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier NIELSEN CHEMICALS
 RAWDON ROAD
 MOIRA
 SWADLINCOTE
 DERBYSHIRE
 DE12 6DA
 TEL: +44 (0) 1283 222277
 FAX: +44 (0) 1283 225731
 info@nielsenchemicals.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs). +44 (0) 1865 407333 (24 hrs). MEDICAL AND ENVIRONMENTAL EMERGENCIES ONLY.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram



Signal word

Danger

SUPER A-SHEEN

| | |
|---------------------------------------|--|
| Hazard statements | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. |
| Precautionary statements | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P501 Dispose of contents/ container in accordance with national regulations. |
| Supplemental label information | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Contains | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|--|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 30-60% |
| CAS number: 64742-82-1 | EC number: 919-446-0 |
| | REACH registration number: 01-2119458049-33-XXXX |
| Classification | |
| Flam. Liq. 3 - H226 | |
| STOT SE 3 - H336 | |
| STOT RE 1 - H372 | |
| Asp. Tox. 1 - H304 | |
| Aquatic Chronic 2 - H411 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Show this Safety Data Sheet to the medical personnel. |
| Inhalation | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. |
| Ingestion | Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention. |
| Skin contact | Wash skin thoroughly with soap and water. Use suitable lotion to moisturise skin. |
| Eye contact | Rinse with water. Remove any contact lenses and open eyelids wide apart. Continue to rinse. Get medical attention if any discomfort continues. |

SUPER A-SHEEN

4.2. Most important symptoms and effects, both acute and delayed

| | |
|---------------------|--|
| Inhalation | May cause drowsiness or dizziness. May cause drowsiness or dizziness. |
| Ingestion | Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Central nervous system depression. |
| Skin contact | Repeated exposure may cause skin dryness or cracking. |
| Eye contact | May cause discomfort. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Provide adequate ventilation. Take precautionary measures against static discharges. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Toxic to aquatic life with long lasting effects.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

SUPER A-SHEEN

7.1. Precautions for safe handling

Usage precautions

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Avoid release to the environment. Do not spray on an open flame or other ignition source. Do not reuse empty containers. Do not use in paint spraying equipment. Do not empty into drains. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures between 4°C and 40°C.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

WEL = Workplace Exposure Limit

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)

DNEL

Workers - Inhalation; Long term systemic effects: 330 mg/m³
 Workers - Dermal; Long term systemic effects: 44 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 71 mg/m³
 Consumer - Dermal; Long term systemic effects: 26 mg/kg/day
 Consumer - Oral; Long term systemic effects: 26 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

SUPER A-SHEEN

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Protective gloves should have a minimum thickness of 0.12 mm. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. For work of short duration or where a high degree of manual dexterity is needed, use protective gloves made of: Nitrile rubber. Neoprene. Rubber (natural, latex). Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use.

Hygiene measures

Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|------------------|---------------------------------|
| Appearance | Liquid. |
| Colour | Colourless. |
| Odour | Solvent. |
| pH | Not applicable. |
| Flash point | 42°C Pensky-Martens closed cup. |
| Relative density | 0.82 @ 20°C |
| Solubility(ies) | Immiscible with water. |
| Viscosity | 525 cP @ 25°C |

9.2. Other information

| | |
|-------------------|-----------------|
| Other information | Not determined. |
|-------------------|-----------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|------------|---|

10.2. Chemical stability

| | |
|-----------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|-----------|---|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|-----------------|
| Possibility of hazardous reactions | Not determined. |
|------------------------------------|-----------------|

10.4. Conditions to avoid

| | |
|---------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. |
|---------------------|---|

10.5. Incompatible materials

SUPER A-SHEEN

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Specific target organ toxicity - repeated exposure

Target organs Central nervous system

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Kinematic viscosity $\leq 20.5 \text{ mm}^2/\text{s}$.

Inhalation May cause drowsiness or dizziness.

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Central nervous system depression.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May cause discomfort.

Toxicological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 15,000.0
mg/kg

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 3,400.0
mg/kg

Species Rat

ATE dermal (mg/kg) 3,400.0

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 1056 mg/kg, Oral, Rat

Target organs Central nervous system

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

SUPER A-SHEEN

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: <30 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: <22 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 4.6-10 mg/l, Algae

Acute toxicity - microorganisms EC₅₀, 48 hours: 43.98 mg/l,

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.097 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

Special Provisions note

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

SUPER A-SHEEN

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.
Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

SUPER A-SHEEN

| | |
|---|--|
| Abbreviations and acronyms used in the safety data sheet | <p>ATE: Acute Toxicity Estimate.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>GHS: Globally Harmonized System.</p> <p>IATA: International Air Transport Association.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>PNEC: Predicted No Effect Concentration.</p> <p>REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>NOEC: No Observed Effect Concentration.</p> <p>UN: United Nations.</p> |
| Revision comments | NOTE: Lines within the margin indicate significant changes from the previous revision. |
| Revision date | 09/05/2018 |
| Revision | 3.1 |
| Supersedes date | 13/06/2017 |
| SDS number | 26503 |
| Hazard statements in full | <p>H226 Flammable liquid and vapour.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.