



NIELSEN

SAFETY DATA SHEET PREMIUM GOLD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PREMIUM GOLD

Internal identification L561

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish.

Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier NIELSEN CHEMICALS
 RAWDON ROAD
 MOIRA
 SWADLINCOTE
 DERBYSHIRE
 DE12 6DA
 TEL: +44 (0) 1283 222277
 FAX: +44 (0) 1283 225731
 info@nielsenchemicals.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs). +44 (0) 1865 407333 (24 hrs). MEDICAL AND ENVIRONMENTAL EMERGENCIES ONLY.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 STOT RE 1 - H372

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) R10,R52/53,R66.

2.2. Label elements

Pictogram



Signal word

Danger

PREMIUM GOLD

Hazard statements	<p>H226 Flammable liquid and vapour.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	<p>EUH066 Repeated exposure may cause skin dryness or cracking.</p>
Contains	<p>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	10-30%
<p>CAS number: 64742-82-1 EC number: 919-446-0 REACH registration number: 01-2119458049-33-XXXX</p>	
<p>Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411</p>	<p>Classification (67/548/EEC or 1999/45/EC) Xn;R65. N;R51/53. R10,R66,R67.</p>
ALUMINIUM HYDROXIDE	1-5%
<p>CAS number: 21645-51-2 EC number: 244-492-7 REACH registration number: 01-2119529246-39-0008</p>	
<p>Classification Not Classified</p>	<p>Classification (67/548/EEC or 1999/45/EC) -</p>
TREATED KAOLIN	1-5%
<p>CAS number: 1332-58-7 EC number: 310-127-6</p>	
<p>Classification Not Classified</p>	<p>Classification (67/548/EEC or 1999/45/EC) -</p>

PREMIUM GOLD

ALUMINIUM SILICATE		1-5%
CAS number: 1344-28-1	EC number: 215-691-6	REACH registration number: 01-2119529248-35-XXXX
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6		<1%
CAS number: 55965-84-9	M factor (Acute) = 10	M factor (Chronic) = 10
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) T;R23/24/25 C;R34 R43 N;R50/53	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues. Use suitable lotion to moisturise skin.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse. Get medical attention if symptoms are severe or persist.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause drowsiness or dizziness.
Ingestion	Central nervous system depression. Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking. May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

PREMIUM GOLD

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂). Silicon.

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near spillage. Take precautionary measures against static discharges. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Provide adequate ventilation. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Do not empty into drains. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Avoid release to the environment. Do not reuse empty containers. Do not empty into drains. Do not eat, drink or smoke when using this product. Do not use in paint spraying equipment. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures between 4°C and 40°C.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

PREMIUM GOLD

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

TREATED KAOLIN

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

ALUMINIUM SILICATE

Short-term exposure limit (15-minute): 10 mg/m³ resp.dust

WEL = Workplace Exposure Limit

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)

DNEL

Workers - Inhalation; Long term systemic effects: 330 mg/m³

Workers - Dermal; Long term systemic effects: 44 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 71 mg/m³

Consumer - Dermal; Long term systemic effects: 26 mg/kg/day

Consumer - Oral; Long term systemic effects: 26 mg/kg/day

ALUMINIUM HYDROXIDE (CAS: 21645-51-2)

DNEL

Workers - Inhalation; Long term systemic effects: 10.76 mg/m³

Workers - Inhalation; Long term local effects: 10.76 mg/m³

General population - Oral; Long term systemic effects: 4.74 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

PREMIUM GOLD

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. Protective gloves should have a minimum thickness of 0.1 mm. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. For work of short duration or where a high degree of manual dexterity is needed, use protective gloves made of: Nitrile rubber. Neoprene. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application.

Hygiene measures

Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Creamy liquid.
Colour	Yellow.
Odour	Pleasant, agreeable.
pH	Not applicable.
Flash point	> 38°C Pensky-Martens closed cup.
Relative density	0.98 @ 25°C
Solubility(ies)	Insoluble in water.
Viscosity	25000 - 35000 cP @ 25°C

9.2. Other information

Other information	Not determined.
-------------------	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
------------------------------------	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with flammable/combustible materials.
--------------------	---

PREMIUM GOLD

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances:
Carbon monoxide (CO). Carbon dioxide (CO₂). Silicon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Specific target organ toxicity - repeated exposure

Target organs Central nervous system

Inhalation May cause drowsiness or dizziness.

Ingestion Central nervous system depression. Gastrointestinal symptoms, including upset stomach.

Skin contact Repeated exposure may cause skin dryness or cracking. May cause skin sensitisation or allergic reactions in sensitive individuals.

Eye contact May cause discomfort.

Toxicological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,400.0

Species Rat

ATE dermal (mg/kg) 3,400.0

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 1056 mg/kg, Oral, Rat

Target organs Central nervous system

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

ALUMINIUM HYDROXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.01

Species Rat

ATE oral (mg/kg) 2,000.01

Acute toxicity - inhalation

PREMIUM GOLD

Acute toxicity inhalation 7.6
(LC₅₀ dust/mist mg/l)

Species Rat

ATE inhalation 7.6
(dusts/mists mg/l)

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 53.0
mg/kg)

Species Rat

Notes (oral LD₅₀) Estimated value.

ATE oral (mg/kg) 53.0

Acute toxicity - dermal

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

ATE inhalation (vapours 3.0
mg/l)

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

SECTION 12: Ecological Information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: <30 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: <22 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 4.6-10 mg/l, Algae

Acute toxicity - microorganisms EC₅₀, 48 hours: 43.98 mg/l,

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.097 mg/l, Daphnia magna

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

PREMIUM GOLD

Acute aquatic toxicity

LE(C)₅₀	0.01 < L(E)C ₅₀ ≤ 0.1
M factor (Acute)	10
Acute toxicity - fish	Estimated value. LC ₅₀ , 96 hours: 13 mg/l, Fish

Chronic aquatic toxicity

NOEC	0.001 < NOEC ≤ 0.01
Degradability	Non-rapidly degradable
M factor (Chronic)	10

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

Special Provisions note

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

14.3. Transport hazard class(es)

PREMIUM GOLD

ADR/RID class	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010. Commission Regulation (EU) No 2015/830 of 28 May 2015.
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

PREMIUM GOLD

Abbreviations and acronyms used in the safety data sheet	<p>ATE: Acute Toxicity Estimate.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>CAS: Chemical Abstracts Service.</p> <p>DNEL: Derived No Effect Level.</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>IATA: International Air Transport Association.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>NOAEL: No Observed Adverse Effect Level.</p> <p>NOEC: No Observed Effect Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>UN: United Nations.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	29/08/2017
Revision	3.1
Supersedes date	30/08/2016
SDS number	24931
Risk phrases in full	<p>Not classified.</p> <p>R10 Flammable.</p> <p>R22 Harmful if swallowed.</p> <p>R38 Irritating to skin.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R66 Repeated exposure may cause skin dryness or cracking.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>H226 Flammable liquid and vapour.</p> <p>H301 Toxic if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H311 Toxic in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H331 Toxic if inhaled.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.</p>

PREMIUM GOLD

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.