

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Exhibition Wax
L066
- Other means of identification:**
EXW001/04
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Auxiliary product for the automotive; water repeller; automotive applications. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Nielsen Chemicals
Rawdon Road, Moira,
DE12 6DA, Swadlincote - Derbyshire - United Kingdom
Phone: 01283 222277
info@nielsenchemicals.com
www.nielsenchemicals.com
- 1.4 Emergency telephone number:** For 24/7 multilingual advice for spill, leak, fire, exposure, or accident Call CHEMTREC at +44 20 3885 0382 / +44 20 3807 3798 and provide CCN 1018675; NPIS: 0844 892 0111 (healthcare professionals only) or NHS 111.

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411
Flam. Liq. 3: Flammable liquids, Category 3, H226
STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1 (Inhalation), H372
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Danger
- 
- Hazard statements:**
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260: Do not breathe vapours
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
- Substances that contribute to the classification**
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)
- 2.3 Other hazards:**

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Wax/es

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT RE 1: H372; STOT SE 3: H336; EUH066 - Danger	25 - <50 %
CAS: 61789-77-3	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Skin Corr. 1B: H314 - Danger	<1 %
CAS: 25307-17-9	2,2'-(octadec-9-enylimino)bisethanol (2 EO) Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314 - Danger	<1 %
CAS: 67-63-0	propan-2-ol Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	<1 %
CAS: 55406-53-6	3-iodo-2-propynyl Butylcarbamate Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger	<1 %
CAS: 140-11-4	Benzyl acetate Aquatic Chronic 3: H412	<1 %
CAS: 101-84-8	Diphenyl ether Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319 - Warning	<1 %
CAS: 84-66-2	Diethyl phthalate	<1 %
CAS: 99-87-6	p-cymene Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Repr. 2: H361 - Danger	<1 %
CAS: 55965-84-9	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<1 %
CAS: 76-22-2	Bornan-2-one Acute Tox. 4: H332; Eye Dam. 1: H318; Flam. Sol. 2: H228; Skin Irrit. 2: H315; STOT SE 2: H371 - Danger	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Bornan-2-one CAS: 76-22-2	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation	1.5 mg/L (4 h)	Rat
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides CAS: 61789-77-3	LD50 oral	960 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation	Not relevant	
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	LD50 oral	1260 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation	Not relevant	
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6	LD50 oral	1100 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation	Not relevant	

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9	LD50 oral	64 mg/kg	Rat
	LD50 dermal	87.12 mg/kg	Rabbit
	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit, ...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:**A.- Specific storage requirements**

Minimum Temp.: 4 °C

Maximum Temp.: 40 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	WEL (15 min)	WEL (8h)
propan-2-ol CAS: 67-63-0	400 ppm	500 ppm	999 mg/m ³ 1250 mg/m ³
Diphenyl ether CAS: 101-84-8	1 ppm	2 ppm	7 mg/m ³ 14 mg/m ³
Diethyl phthalate CAS: 84-66-2			5 mg/m ³ 10 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1 EC: 919-446-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	21 mg/kg	Not relevant
	Inhalation	570 mg/m ³	Not relevant	330 mg/m ³	Not relevant
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9 EC: 246-807-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.42 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2.96 mg/m ³	Not relevant
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	888 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	500 mg/m ³	Not relevant
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	2 mg/kg	Not relevant
	Inhalation	0.07 mg/m ³	1.16 mg/m ³	0.023 mg/m ³	1.16 mg/m ³
Benzyl acetate CAS: 140-11-4 EC: 205-399-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	2.5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	9 mg/m ³	Not relevant
Diphenyl ether CAS: 101-84-8 EC: 202-981-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
	Inhalation	Not relevant	14 mg/m ³	59 mg/m ³	7 mg/m ³
Diethyl phthalate CAS: 84-66-2 EC: 201-550-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	15 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	10.56 mg/m ³	Not relevant
p-cymene CAS: 99-87-6 EC: 202-796-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.25 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.88 mg/m ³	Not relevant
Bornan-2-one CAS: 76-22-2 EC: 200-945-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	10 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	17.632 mg/m ³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1 EC: 919-446-0	Oral	Not relevant	Not relevant	21 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	12 mg/kg	Not relevant
	Inhalation	570 mg/m ³	Not relevant	71 mg/m ³	Not relevant
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9 EC: 246-807-3	Oral	Not relevant	Not relevant	0.15 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0.15 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.522 mg/m ³	Not relevant

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Not relevant	Not relevant	26 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	319 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	89 mg/m ³	Not relevant
Benzyl acetate CAS: 140-11-4 EC: 205-399-7	Oral	Not relevant	Not relevant	1.3 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	1.3 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2.2 mg/m ³	Not relevant
Diethyl phthalate CAS: 84-66-2 EC: 201-550-6	Oral	Not relevant	Not relevant	0.75 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	7.5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2.6 mg/m ³	Not relevant
p-cymene CAS: 99-87-6 EC: 202-796-7	Oral	Not relevant	Not relevant	0.125 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0.125 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.22 mg/m ³	Not relevant
Bornan-2-one CAS: 76-22-2 EC: 200-945-0	Oral	Not relevant	Not relevant	5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4.348 mg/m ³	Not relevant

PNEC:

Identification					
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9 EC: 246-807-3	STP	1.5 mg/L	Fresh water	0.00016 mg/L	
	Soil	5 mg/kg	Marine water	0.000016 mg/L	
	Intermittent	0.00043 mg/L	Sediment (Fresh water)	1.692 mg/kg	
	Oral	2 g/kg	Sediment (Marine water)	0.169 mg/kg	
propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2251 mg/L	Fresh water	140.9 mg/L	
	Soil	28 mg/kg	Marine water	140.9 mg/L	
	Intermittent	140.9 mg/L	Sediment (Fresh water)	552 mg/kg	
	Oral	0.16 g/kg	Sediment (Marine water)	552 mg/kg	
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5	STP	0.44 mg/L	Fresh water	0.001 mg/L	
	Soil	0.005 mg/kg	Marine water	0 mg/L	
	Intermittent	0.001 mg/L	Sediment (Fresh water)	0.017 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.002 mg/kg	
Benzyl acetate CAS: 140-11-4 EC: 205-399-7	STP	8.55 mg/L	Fresh water	0.018 mg/L	
	Soil	0.094 mg/kg	Marine water	0.002 mg/L	
	Intermittent	0.04 mg/L	Sediment (Fresh water)	0.526 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.053 mg/kg	
Diphenyl ether CAS: 101-84-8 EC: 202-981-2	STP	10 mg/L	Fresh water	0 mg/L	
	Soil	0.018 mg/kg	Marine water	0 mg/L	
	Intermittent	0.005 mg/L	Sediment (Fresh water)	0.093 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.009 mg/kg	
Diethyl phthalate CAS: 84-66-2 EC: 201-550-6	STP	2 mg/L	Fresh water	0.012 mg/L	
	Soil	0.137 mg/kg	Marine water	0.0012 mg/L	
	Intermittent	0.12 mg/L	Sediment (Fresh water)	0.137 mg/kg	
	Oral	0.033 g/kg	Sediment (Marine water)	0.0137 mg/kg	
p-cymene CAS: 99-87-6 EC: 202-796-7	STP	10 mg/L	Fresh water	0.004 mg/L	
	Soil	0.302 mg/kg	Marine water	0 mg/L	
	Intermittent	0.037 mg/L	Sediment (Fresh water)	1.52 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.152 mg/kg	
Bornan-2-one CAS: 76-22-2 EC: 200-945-0	STP	1 mg/L	Fresh water	0.00171 mg/L	
	Soil	0.013 mg/kg	Marine water	0.000171 mg/L	
	Intermittent	0.0171 mg/L	Sediment (Fresh water)	0.139 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.017 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

In accordance with the order of importance to control professional exposure it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: A2, FFP1)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.062 mm, Conditions of use: Splashing)	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Emulsion
Colour:	White
Odour:	Pleasant
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	111 °C
Vapour pressure at 20 °C:	2222 Pa
Vapour pressure at 50 °C:	11736.62 Pa (11.74 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1001.1 kg/m ³
Relative density at 20 °C:	0.95 - 0.96
Dynamic viscosity at 20 °C:	40000 - 60000 cP
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>20.5 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	>37 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	202 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1	>5100 mg/kg	>3160 mg/kg	Rat
	>20 mg/L (4 h)		Rabbit
			Rat
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides CAS: 61789-77-3	960 mg/kg	>5000 mg/kg	Rat
	>20 mg/L		
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	1260 mg/kg	>5000 mg/kg	Rat
	>20 mg/L		
propan-2-ol CAS: 67-63-0	5280 mg/kg	12800 mg/kg	Rat
	72.6 mg/L (4 h)		Rat
			Rat
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6	1100 mg/kg	2100 mg/kg	Rat
	>5 mg/L		Rabbit
Benzyl acetate CAS: 140-11-4	2490 mg/kg	>5000 mg/kg	Rat
	>20 mg/L		
Diphenyl ether CAS: 101-84-8	>5000 mg/kg	7940 mg/kg	Rat
	>5 mg/L		Rabbit
Diethyl phthalate CAS: 84-66-2	>5000 mg/kg	>5000 mg/kg	
	>20 mg/L		
p-cymene CAS: 99-87-6	4750 mg/kg	>5000 mg/kg	Rat
	>20 mg/L		Rabbit
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9	64 mg/kg	87.12 mg/kg	Rat
	0.33 mg/L (4 h)		Rabbit
			Rat
Bornan-2-one CAS: 76-22-2	>5000 mg/kg	>5000 mg/kg	
	1.5 mg/L (4 h)		
			Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides CAS: 61789-77-3	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	LC50	0.1 mg/L (96 h)	Danio rerio	Fish
	EC50	0.043 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0.0867 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
propan-2-ol CAS: 67-63-0	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6	LC50	0.07 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.09 mg/L (96 h)	Mysidopsis bahia	Crustacean
	EC50	0.05 mg/L (72 h)	Scenedesmus subspicatus	Algae
Benzyl acetate CAS: 140-11-4	LC50	Not relevant		
	EC50	17 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	110 mg/L (72 h)	Desmodesmus subspicatus	Algae
Diphenyl ether CAS: 101-84-8	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Diethyl phthalate CAS: 84-66-2	LC50	61 mg/L (48 h)	Leuciscus idus	Fish
	EC50	52 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
p-cymene CAS: 99-87-6	LC50	48 mg/L (96 h)	Cyprionodon variegatus	Fish
	EC50	3.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Bornan-2-one CAS: 76-22-2	LC50	110 mg/L (96 h)	Pimephales promelas	Fish
	EC50	4.2 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1.71 mg/L (72 h)	N/A	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides CAS: 61789-77-3	NOEC	Not relevant		
	NOEC	0.15 mg/L	Daphnia magna	Crustacean
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	NOEC	Not relevant		
	NOEC	0.0099 mg/L	Daphnia magna	Crustacean
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6	NOEC	0.0084 mg/L	Pimephales promelas	Fish
	NOEC	0.0499 mg/L	Daphnia magna	Crustacean
Benzyl acetate CAS: 140-11-4	NOEC	0.92 mg/L	Oryzias latipes	Fish
	NOEC	Not relevant		
Diethyl phthalate CAS: 84-66-2	NOEC	5 mg/L	Cyprinus carpio	Fish
	NOEC	25 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides CAS: 61789-77-3	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	82 %
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	BOD5	Not relevant	Concentration	10 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
propan-2-ol CAS: 67-63-0	BOD5	1.19 g O ₂ /g	Concentration	100 mg/L
	COD	2.23 g O ₂ /g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %
Benzyl acetate CAS: 140-11-4	BOD5	Not relevant	Concentration	10 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	100 %
Diphenyl ether CAS: 101-84-8	BOD5	Not relevant	Concentration	5.6 mg/L
	COD	Not relevant	Period	20 days
	BOD5/COD	Not relevant	% Biodegradable	76 %
Diethyl phthalate CAS: 84-66-2	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
p-cymene CAS: 99-87-6	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
Bornan-2-one CAS: 76-22-2	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	94 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
propan-2-ol CAS: 67-63-0	BCF	3
	Pow Log	0.05
	Potential	Low
3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6	BCF	36
	Pow Log	2.4
	Potential	Moderate
Benzyl acetate CAS: 140-11-4	BCF	8
	Pow Log	1.96
	Potential	Low
Diphenyl ether CAS: 101-84-8	BCF	196
	Pow Log	4.21
	Potential	High
Diethyl phthalate CAS: 84-66-2	BCF	117
	Pow Log	2.07
	Potential	High
p-cymene CAS: 99-87-6	BCF	286
	Pow Log	4.1
	Potential	High
Bornan-2-one CAS: 76-22-2	BCF	38
	Pow Log	2.38
	Potential	Moderate

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
2,2'-(octadec-9-enylimino)bisethanol (2 EO) CAS: 25307-17-9	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	2.8E-2 N/m (25 °C)	Moist soil	Not relevant
propan-2-ol CAS: 67-63-0	Koc	1.5	Henry	8.207E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.24E-2 N/m (25 °C)	Moist soil	Yes
Benzyl acetate CAS: 140-11-4	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	3.558E-2 N/m (25 °C)	Moist soil	Not relevant
Diphenyl ether CAS: 101-84-8	Koc	1960	Henry	Not relevant
	Conclusion	Low	Dry soil	Not relevant
	Surface tension	1.753E-2 N/m (258.4 °C)	Moist soil	Not relevant
Diethyl phthalate CAS: 84-66-2	Koc	Not relevant	Henry	6.181E-2 Pa·m ³ /mol
	Conclusion	Not relevant	Dry soil	No
	Surface tension	3.699E-2 N/m (25 °C)	Moist soil	No
p-cymene CAS: 99-87-6	Koc	5011.87	Henry	1114.58 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Not relevant
	Surface tension	2.835E-2 N/m (25 °C)	Moist soil	Yes
Bornan-2-one CAS: 76-22-2	Koc	470	Henry	8.21 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Not relevant
	Surface tension	1.53E-3 N/m (307.98 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
16 05 08*	discarded organic chemicals consisting of or containing hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Marine pollutant: Yes
14.6 Special precautions for user
 Special regulations: 274
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 0
 Segregation group: Not relevant
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- 14.1 UN number:** UN1993
14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: I
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.
Control of Substances Hazardous to Health Regulations 2002 (as amended)
EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.
H372: Causes damage to organs through prolonged or repeated exposure (Inhalation).
H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.
Acute Tox. 3: H301 - Toxic if swallowed.
Acute Tox. 3: H331 - Toxic if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Flam. Sol. 2: H228 - Flammable solid.
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
STOT SE 2: H371 - May cause damage to organs.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method
Aquatic Chronic 2: Calculation method
STOT RE 1: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- CONTINUED ON NEXT PAGE -

**Exhibition Wax
L066**

Date of compilation: 24/04/2023 Revised: 22/07/2024 Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)<http://echa.europa.eu><http://eur-lex.europa.eu>**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -