


**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** Super A-Sheen  
L431
- Other means of identification:**  
000380
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Auxiliary product for the automotive. For professional users/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Nielsen Chemicals  
Rawdon Road, Moira,  
DE12 6DA, Swadlincote - Derbyshire - United Kingdom  
Phone: 01283 222277  
info@nielsenchemicals.com  
www.nielsenchemicals.com
- 1.4 Emergency telephone number:** For 24/7 multilingual advice for spill, leak, fire, exposure, or accident Call CHEMTREC at +44 20 3885 0382 / +44 20 3807 3798 and provide CCN 1018675; NPIS: 0844 892 0111 (healthcare professionals only) or NHS 111.

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**  
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Asp. Tox. 1: Aspiration hazard, Category 1, H304  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1 (Inhalation), H372  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**  
Danger
- 
- Hazard statements:**  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).  
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves.  
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P310: Immediately call a POISON CENTER/doctor.  
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**  
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 2: HAZARDS IDENTIFICATION (continued)****2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substance:**

Non-applicable

**3.2 Mixture:****Chemical description:** Mixture of substances**Components:**

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 64742-82-1	<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b> Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT RE 1: H372; STOT SE 3: H336; EUH066 - Danger	50 - <75 %
CAS: 112-53-8	<b>Dodecan-1-ol</b> Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Irrit. 2: H319 - Warning	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 5: FIREFIGHTING MEASURES (continued)****Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**B.- Technical recommendations for the prevention of fires and explosions**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023      Revised: 30/07/2024      Version: 3 (Replaced 2)

**SECTION 7: HANDLING AND STORAGE (continued)**

**D.- Technical recommendations to prevent environmental risks**

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Specific storage requirements**

Minimum Temp.: 4 °C

Maximum Temp.: 40 °C

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1 EC: 919-446-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	21 mg/kg	Not relevant
	Inhalation	570 mg/m <sup>3</sup>	Not relevant	330 mg/m <sup>3</sup>	Not relevant
Dodecan-1-ol CAS: 112-53-8 EC: 203-982-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	89 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	313 mg/m <sup>3</sup>	155 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1 EC: 919-446-0	Oral	Not relevant	Not relevant	21 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	12 mg/kg	Not relevant
	Inhalation	570 mg/m <sup>3</sup>	Not relevant	71 mg/m <sup>3</sup>	Not relevant
Dodecan-1-ol CAS: 112-53-8 EC: 203-982-0	Oral	Not relevant	Not relevant	44.5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	44.5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	77 mg/m <sup>3</sup>	Not relevant

**PNEC:**

Identification					
Dodecan-1-ol CAS: 112-53-8 EC: 203-982-0	STP	Not relevant	Fresh water	0.001 mg/L	
	Soil	0.132 mg/kg	Marine water	0 mg/L	
	Intermittent	Not relevant	Sediment (Fresh water)	0.666 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.067 mg/kg	

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -


**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)


**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

In accordance with the order of importance to control professional exposure it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: A2, FFP1)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**C.- Specific protection for the hands**



Pictogram	PPE	Remarks
 Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile/Neoprene, Breakthrough time: > 480 min, Thickness: 0.15 mm, Conditions of use: Splashing)	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



**D.- Eye and face protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Greasy
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not relevant *

**Volatility:**

Boiling point at atmospheric pressure:	150 °C (ASTM D 1120-72)
Vapour pressure at 20 °C:	198 Pa
Vapour pressure at 50 °C:	1556.07 Pa (1.56 kPa)
Evaporation rate at 20 °C:	Not relevant *

**Product description:**

Density at 20 °C:	842 kg/m <sup>3</sup>
Relative density at 20 °C:	0.81 - 0.83
Dynamic viscosity at 20 °C:	300 - 900 cP
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	~20 mm <sup>2</sup> /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

**Flammability:**

Flash Point:	>42 °C (Pensky-Martins (CC))
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	275 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *
<b>Other safety characteristics:</b>	
Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Repeated exposure may cause skin dryness or cracking

**H- Aspiration hazard:**

May be fatal if swallowed and enters airways.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Value	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1	LD50 oral	>5100 mg/kg	Rat
	LD50 dermal	>3160 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	Rat
Dodecan-1-ol CAS: 112-53-8	LD50 oral	26530 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration	Species	Genus
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 64742-82-1	LC50	>1 - 10 mg/L (96 h)	Fish
	EC50	>1 - 10 mg/L (48 h)	Crustacean
	EC50	>1 - 10 mg/L (72 h)	Algae
Dodecan-1-ol CAS: 112-53-8	LC50	1.01 mg/L (96 h)	Pimephales promelas
	EC50	320 mg/L (48 h)	Daphnia magna
	EC50	0.97 mg/L (96 h)	Scenedesmus subspicatus

**Chronic toxicity:**

Identification	Concentration	Species	Genus
Dodecan-1-ol CAS: 112-53-8	NOEC	0.26 mg/L	Pimephales promelas
	NOEC	0.014 mg/L	Daphnia magna

**12.2 Persistence and degradability:**

Not available

- CONTINUED ON NEXT PAGE -



**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Dodecan-1-ol	BCF	180
CAS: 112-53-8	Pow Log	5.13
	Potential	High

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Dodecan-1-ol	Koc	15000	Henry	2.25 Pa·m <sup>3</sup> /mol
CAS: 112-53-8	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	2.94E-2 N/m (25 °C)	Moist soil	Yes

Insoluble in water

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

**Type of waste:**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



- 14.1 UN number:** UN1993
- 14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
- 14.3 Transport hazard class(es):** 3
- Labels:** 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
- Tunnel restriction code: D/E
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Not relevant

**Transport of dangerous goods by sea:**

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 14: TRANSPORT INFORMATION (continued)**

With regard to IMDG 41-22:



<b>14.1 UN number:</b>	UN1993
<b>14.2 UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Marine pollutant:</b>	Yes
<b>14.6 Special precautions for user</b>	
Special regulations:	274, 223, 955
EmS Codes:	F-E, S-E
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
Segregation group:	Not relevant
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



<b>14.1 UN number:</b>	UN1993
<b>14.2 UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Environmental hazards:</b>	Yes
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Not relevant

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

**Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ...):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.  
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.  
Control of Substances Hazardous to Health Regulations 2002 (as amended)  
EH40/2005 Workplace exposure limits.

**SECTION 16: OTHER INFORMATION**

Legislation related to safety data sheets:

- CONTINUED ON NEXT PAGE -

**Super A-Sheen  
L431**

Date of compilation: 18/04/2023    Revised: 30/07/2024    Version: 3 (Replaced 2)

**SECTION 16: OTHER INFORMATION (continued)**

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

**Texts of the legislative phrases mentioned in section 2:**

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H372: Causes damage to organs through prolonged or repeated exposure (Inhalation).

H304: May be fatal if swallowed and enters airways.

H226: Flammable liquid and vapour.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

STOT SE 3: Calculation method

Aquatic Chronic 2: Calculation method

STOT RE 1: Calculation method

Asp. Tox. 1: Calculation method

Flam. Liq. 3: On basis of test data

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -